

PRODUCT DATA SHEET



TSS 005 ALL GLASS LOW SPALL 1-1/2"

MODEL#: 0-GLZ-TIG-1008

PRODUCT LINE: GLAZING

DESCRIPTION

Total Security Solutions' premium all-glass security glazing combines clarity with uncompromising protection. Designed to resist ballistic threats and various physical attacks, these high-performance units feature multiple layers of laminated glass fused with advanced polyurethane or polyvinyl interlayers for superior strength and clarity. Independently tested to the demanding UL 752 standard, Total Security Solutions' all-glass security glazing delivers the trusted protection your space deserves—without sacrificing on aesthetics.

OPTIONS

- Tinted glass (gray, bronze, green, blue)
- Reflective glass
- One-way mirror
- Translucent white interlayer (frosted glass)
- Wire glass
- Insulated units
- Low E
- Please inquire for additional options

RATINGS

- U.L. 752 - Level 5
 - Projectile Type: 150 grain 7.62mm lead core full metal copper jacket military ball
 - Velocity Range: 2,750 fps to 3,025 fps
 - Number of Shots: 1

STANDARDS

- U.L. 752 Standard for Bullet Resistant Materials
- ASTM C1036 Standard Specification for Flat Glass
- ASTM C1172 Standard Specification for Laminated Architectural Flat Glass

THREAT SIDE	SECURE SIDE
<ol style="list-style-type: none">1. Glass2. Interlayer3. Glass4. Interlayer5. Glass6. Interlayer7. Glass8. Interlayer9. Glass	<p>Tints and Mirrors applied to layer 2</p> <p>Low E applied to layers 2 or 3</p>

PROPERTIES

Nominal Thickness	1 1/2"
Thickness Tolerance	±3/32"
Weight	18.74 lbs/sqft
Maximum Size	72" x 140"
Dimensional Tolerance	±1/16"
Visible Light Transmittance	75%
U-Value	0.75
SHGC	0.58