

**COMPONENTS**

- Threat Layer 1: 1/8" Mar Resistant Polycarbonate
- Layer 2: .025 Urethane
- Layer 3: 1" Acrylic
- Layer 4: .025 Urethane
- Secure Layer 5: 1/8" Mar Resistant Polycarbonate

**LAMINATED POLYCARBONATE**

**PRODUCT: LP 1250 BR 1 1/4"**



**PROPERTIES & SPECIFICATIONS**

Protection	.44 Mag
Ballistic Data	Velocity 1: 1350 ft/s Velocity 2: 1485 ft/s
Shots	3
Light Transmission	77.00%
Thickness	1.25 "
Weight	7.7 lbs/sqft
Dimensional Tolerance	ASTM C 1349

**STANDARDS**

- NSI Z971-1984 Safety Glazing Materials for Building
- ASTM C 1036 Standard Specifications for Flat Glass
- ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

**HANDLING INFORMATION**

It is imperative to clean the glazing unit during and after the construction period to maintain optimum performance and aesthetic properties. To clean, use a soft, clean cloth and a mild soap, detergent, or slightly acidic cleaning solution (such as vinegar). Wipe with a clean, lint-free cloth.

**STANDARD WARRANTY**

12-month limited warranty. Does not cover damage from neglect, abuse, vandalism, improper maintenance, or any other cause not arising out of defects in material or workmanship. The warranties stated replace and exclude all other warranties. The warranty is limited to replacing products that fail to meet specification, defective in quality, or workmanship at time of delivery. TSS is not responsible for (re)installation expenses or any direct or indirect losses which may result from a defective product. TSS reserves the right to field inspect any product alleged to be defective. Buyer is responsible for any consequences from product use.

**BALLISTIC AND FORCED ENTRY RATING**

- H.P. White TP-0500.01 Level IV –Forced Entry
- H.P. White Level C Ballistics - .44 Mag
- U.L. Level 3 – .44 Mag
- U.L. Level 6 – 9 mm Rifle
- NIJ STD-0108.01 Level IIIA - .44 Mag
- WMFL Level - .44 Mag

**TOTAL SECURITY SOLUTIONS**

P: 517.223.7807 | info@tssbulletproof.com | F. 517.223.0805 | 935 Garden Lane, Fowlerville, MI

Proprietary information not for public distribution